



# Ultracoat Top Deck Cleaner

Ready-to-use alkaline solution used for maintenance work on external wooden decking treated with Ultracoat Top Deck Oil



## WHERE TO USE

Combat discoloration and remove dirt from all types of external wooden decking without harming the sealant in expansion joints.

## TECHNICAL CHARACTERISTICS

**Ultracoat Top Deck Cleaner** is a solution used to revive external wooden decking that have been discoloured by the weather.

## RECOMMENDATIONS

- Do not use **Ultracoat Top Deck Cleaner** at temperatures lower than +5°C.
- Use only clean containers and tools.
- Do not put remainder of the product back into its original container.

## APPLICATION PROCEDURE

Remove all traces of dirt and dust from the floor.

Remove all traces of dirt and dust from the floor, apply **Ultracoat Top Deck Cleaner** on the floor with a brush or fibre mop and wait 15/20 minutes. Remove the sheen with a medium to stiff brush or a red Scotch-Brite pad. Clean and rinse the floor with clean water and wait until it is completely dry before applying a fresh treatment of **Ultratop Top Deck Oil**.

## Cleaning

Clean tools and traces of **Ultracoat Top Deck Cleaner** immediately after use with warm water and soap.

## CONSUMPTION

Depending on the type of floor.

## STORAGE

12 months in its original packaging in a dry place.

## PACKAGING

4 litres.

## SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

**Ultratop Top Deck Cleaner** is irritant for the skin and eyes. When applying the product, wear protective gloves and goggles and take the usual precautions for the handling of chemicals. If the product comes into contact with the eyes or skin, wash immediately with plenty of clean water and seek medical attention.

For further and complete information about a safe use of our product please refer to our latest version of the Material Safety Data Sheet.

PRODUCT FOR PROFESSIONAL USE.

## WARNING

*Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all*



# Ultracoat Top Deck Cleaner



## TECHNICAL DATA (typical values)

### PRODUCT IDENTITY

#### ALKALINE SOLUTION

pH:	13
Dilution:	3/10 dl in 10 litres of warm water
drying time:	24 hours
cleaning of tools:	soap and warm water

*the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.*

**Please refer to the current version of the Technical Data Sheet, available from our website [www.mapei.com](http://www.mapei.com)**

**All relevant references for the product are available upon request and from [www.mapei.com](http://www.mapei.com)**

